

SAR-1055-12-S2

WR-12 Rectangular Horn Antenna, 10 dBi Gain

SAR-1055-12-S2 is an E-band rectangular horn antenna that operates from 60 GHz to 90 GHz. The antenna offers 10 dBi nominal gain and a typical half power beamwidth of 55 degrees on both E-plane and H-plane, respectively. The antenna supports linear polarized waveforms. The input of this antenna is a WR-12 waveguide with UG-387/U anti-cocking flange.



Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	60 GHz		110 GHz
Gain		10 dBi	
3 dB Beamwidth, E-Plane		55°	
3 dB Beamwidth, H-Plane		55°	
Polarization		Linear	
Sidelobes, E-Plane		-20 dB	
Sidelobes, H-Plane		-20 dB	
Return Loss		20	
Specification Temperature		+25°C	
Operating Temperature	-40°C		+85°C

Mechanical Specifications:

Item	Specification
Antenna Port	WR-12 Waveguide with UG-387/U Anti-Cocking Flange
Material	Brass
Finish	Gold Plated
Weight	0.3 Oz
Outline	AR-E10

ECCN

EAR99

FEATURES

- Rectangular Waveguide Interface
- Precisely Machined and Gold Plated
- Linear Polarization
- High Return Loss


APPLICATIONS

- Antenna Ranges
- Antenna Gain Measurements
- System Setups


SUPPLEMENTAL DETAILS




Simulated Antenna Patterns @ 60 GHz



Simulated Antenna Patterns @ 75 GHz




Simulated Antenna Patterns @ 90 GHz




MAKING MILLIMETERWAVE ACCESSIBLE

Simulated Return Loss vs. Frequency




MAKING MILLIMETERWAVE ACCESSIBLE

Simulated Gain vs. Frequency



Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTE:

- This antenna is a mature product. The reason for only providing simulated data can be found in the following blog [here](#).
- Eravant reserves the right to change the information presented without notice.

CAUTION:

- Any foreign objects in the antenna will cause performance degradation and possible device damage.

ERAVANT
MAKING MILLIMETERWAVE ACCESSIBLE

ERAVANT
MAKING MILLIMETERWAVE ACCESSIBLE