

WR-19 Standard Gain Horn Antenna, 24 dBi Gain, Non Anti-Cocking

Description:

Model SAZ-2410-19-S1-NAC is a U-band standard gain horn antenna that operates from 40 GHz to 60 GHz. The antenna offers 24 dBi nominal gain, a typical half power beamwidth of 9.7 degrees on the E-plane and 11.0 degrees on the H-plane at the center frequency, respectively. The antenna supports linear polarized waveforms. The input of this antenna is a WR-19 waveguide with UG-383/U-M flange. The standard gain horn is offered for antenna range calibration purpose mainly, but it can be also used for general purpose system set ups.



Features:

- Rectangular Waveguide Interface
- Precisely Machined and Gold Plated
- Linear Polarization
- High Return Loss

Applications:

- Antenna Range Standards
- Antenna Gain Measurements
- General System Setups
- Radar/Communication Systems



Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	40 GHz		60 GHz
Gain		24 dBi	
Polarization		Linear	
3 dB Beamwidth, E-Plane @50GHz		9.7°	
3 dB Beamwidth, H-Plane @50GHz		11.0°	
Sidelobes, E-Plane		-13 dB	
Sidelobes, H-Plane		-36 dB	
Return Loss		23 dB	
Specification Temperature		+25 °C	
Operation Temperature	-40 °C		+85 °C

Mechanical Specifications:

Item	Specification
Antenna Port	WR-19 Waveguide
Flange Type	UG-383/U-M Flange
Size	3.90" (L) X 1.75" (W) X 1.42" (H)
Material	Brass
Finish	Gold Plated
Weight	2.78 Oz
Outline	AZ-U24



WR-19 Standard Gain Horn Antenna, 24 dBi Gain, Non Anti-Cocking**Simulated Antenna Patterns @ 50 GHz****Simulated Gain vs. Frequency**



WR-19 Standard Gain Horn Antenna, 24 dBi Gain, Non Anti-Cocking

Simulated Gain vs. Frequency in Tabular Format

Frequency (GHz)	Gain (dBi)	Frequency (GHz)	Gain (dBi)
40	22.8	51	24.3
41	23.1	52	24.2
42	23.1	53	24.4
43	23.3	54	24.5
44	23.4	55	24.5
45	23.6	56	24.7
46	23.7	57	24.7
47	23.8	58	24.7
48	23.9	59	24.9
49	24.0	60	24.8
50	24.1		

Simulated Half Power Beamwidth (H-Plane) vs. Frequency in Tabular Format

Frequency (GHz)	Beamwidth (Degrees)	Frequency (GHz)	Beamwidth (Degrees)
40	12.4	51	10.9
41	12.3	52	10.7
42	12.1	53	10.6
43	11.9	54	10.5
44	11.8	55	10.4
45	11.6	56	10.2
46	11.4	57	10.2
47	11.3	58	10.1
48	11.1	59	9.9
49	11.1	60	10.1
50	10.9		


Simulated Half Power Beamwidth (E-Plane) vs. Frequency in Tabular Format

Frequency (GHz)	Beamwidth (Degrees)	Frequency (GHz)	Beamwidth (Degrees)
40	11.3	51	9.0
41	11.1	52	8.9
42	11.0	53	8.4
43	10.7	54	8.3
44	10.6	55	8.0
45	10.5	56	7.7
46	10.3	57	7.8
47	10.2	58	7.3
48	9.9	59	7.3
49	9.8	60	7.2
50	9.4		



WR-19 Standard Gain Horn Antenna, 24 dBi Gain, Non Anti-Cocking

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- All data presented is simulated by a full EM simulator. Eravant recommends using simulated data over measured for pyramidal horn antenna for accuracy. See Blog [here](#) for further information.
- Eravant reserves the right to change the information presented without notice.

Caution:

- Any foreign objects in the antenna will cause performance degradation and possible device damage.

