



Ka-Band Power Amplifier, 26.5 to 40 GHz, 30 dB Gain, +26 dBm P_{1dB}

Description:

Model SBP-2734033026-2828-E1 is a Ka band power amplifier with a typical small signal gain of 30 dB and a nominal P_{1dB} of +26 dBm across the frequency range of 26.5 to 40 GHz. The DC power requirement for the amplifier is +8 V_{DC}/1,100 mA. The mechanical configuration is an inline structure with WR-28 Uni-Guide™ waveguides. Other port configurations, such as K connectors for either the input or output port, are also available under different model numbers.



Features:

- Full Waveguide Band Coverage
- High Gain
- High Output Power
- Good Power and Gain Flatness

Applications:

- 5G Systems
- Radar Systems
- Communication Systems
- Test Equipment

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	26.5 GHz		40.0 GHz
Gain		30 dB	
P _{1dB}		+26 dBm	
P _{SAT}		+27 dBm	
P _{in}			+15 dBm
Input Return Loss		10 dB	
Output Return Loss		10 dB	
DC Voltage		+8 V _{DC}	+12 V _{DC}
DC Supply Current		1,100 mA	
Specification Temperature		+25 °C	
Operating Temperature	0 °C		+50 °C

Mechanical Specifications:

Item	Specification
Input Port	WR-28 Uni-Guide™ Waveguide with UG-599/U Compatible Flange
Output Port	WR-28 Uni-Guide™ Waveguide with UG-599/U Compatible Flange
Bias	Solder Pin
Case Material	Aluminum
Finish	Gold Plated
Weight	2.0 Oz
Size	2.05" (L) x 1.20" (W) x 0.75" (H)
Outline	BG-SA-2






Ka-Band Power Amplifier, 26.5 to 40 GHz, 30 dB Gain, +26 dBm P_{1dB}


Typical Gain and Return Loss vs. Frequency

Bias = +8 V_{DC}/1,100 mA



Typical Output P_{1dB} and Psat vs. Frequency


Bias: +8 V_{DC}/1,300 mA





Ka-Band Power Amplifier, 26.5 to 40 GHz, 30 dB Gain, +26 dBm P_{1dB}

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- All data presented is collected from a sample lot. Actual data may vary unit to unit.
- All testing was performed under +25 °C case temperature.
- The amplifier employs SAGE Millimeter’s trademarked and patent pending technology, **Uni-Guide™**, as its waveguide interfaces. The orientation of the input and the output waveguides can be specified through corresponding model numbers. For example, the model number for a horizontal output waveguide configuration would be **SBP-2734033026-2828H-E1** instead of the default **SBP-2734033026-2828-E1** which indicates vertical orientation output.
- Other mechanical configurations are available under different model numbers.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

Caution:

- Exceeding absolute maximum ratings shown will damage the device.
- Exceeding the maximum bias voltage of **+12 V_{DC}** will cause amplifier overheating and result the instability.
- The device is static sensitive. Always follow ESD rules when working with the device.



Ka-Band Power Amplifier, 26.5 to 40 GHz, 30 dB Gain, +26 dBm P_{1dB}

- The case temperature of the device shall never exceed +50 °C. Use proper heatsink or fan if necessary.
- Any foreign objects in the waveguide will cause performance degradation and may damage the device.

