

1.85 mm (M) to 1.85 mm (M) Coaxial Cable, Flexible, 7.5"

Description:

Model SCW-VMVM008-F1-7.5-WP is a 7.5" long, flexible, coaxial cable with 1.85 mm (V) male connectors that cover the frequency range of DC to 67 GHz. The coaxial cable utilizes the highest quality test instrumentation grade cable and a precision manufacturing process to guarantee superior microwave performance and mechanical durability. The impedance of the cable is 50 ohms. Other lengths are offered under different models.



Features:

- High Return Loss
- Low Insertion Loss
- Flexible and Durable

Applications:

- Test Lab
- Sub-assemblies

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	DC		67 GHz
Insertion Loss @ 18 GHz		0.7 dB	
Insertion Loss @ 30 GHz		1.01 dB	
Insertion Loss @ 40 GHz		1.27 dB	
Insertion Loss @ 67 GHz		1.76 dB	
Return Loss @ 67 GHz		17 dB	
Impedance		50 Ω	
Breakdown Voltage			500 Volts
Radiation Shielding		100 dB	
Power Handling @ 67 GHz			8 W (CW)
Specification Temperature		+25 °C	
Operating Temperature	-40 °C		+85 °C

Mechanical Specifications:

Item	Specification
Connectors	1.85 mm Male
Connector Contact Material/Plating	Beryllium Copper (BeCu)/Gold Plating Per MIL-G-45204
Connector / Cable Insulation Layer Material	Passivated Stainless Steel / PEEK/PEI
Cable Jacket Material	PFA
Cable Outer Diameter	0.087"
Length	7.5"
Outline	CW-VV-F8



1.85 mm (M) to 1.85 mm (M) Coaxial Cable, Flexible, 7.5"

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches)



Note:

- Length "L" can be customizable.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

Caution:

- Bending the cable sharply will either cause damage or degrade the performance of the cable.
- Proper torque, 8.0 ± 0.15 inch-pounds (0.90 ± 0.02 Nm), should be applied. **SAGE Millimeter torque wrench, model SCH-08008-S1, is highly recommended.**

