

SOP-22310118-SF-EB

Phase Locked Oscillator, 22 GHz, +18 dBm, 100 MHz Externally Referenced

SOP-22310118-SF-EB is a phase locked oscillator with high performance DRVCO (Dielectric Resonator Voltage Controller Oscillator) technology to generate a clean and high-quality microwave signal. The oscillator is designed and fabricated to be phase locked to the high quality 100 MHz externally reference oscillator so that the superior phase noise performance can be achieved. The oscillator delivers a typical output power of +18 dBm and has nominal harmonic of -25 dBc and spurious of -75 dBc, respectively. The oscillator has a built-in voltage regulator to further improve the signal quality and prevent possible damage due to the over voltage operation. The oscillator is hermetically sealed to offer the maximum environmental performance.



Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency		22 GHz	
Output Power		+18 dBm	
Phase Noise*	Reference Source + 20 Log (N) + 3 dB		
External Reference Frequency		100 MHz	
External Reference Input Power	-3 dBm	0 dBm	+3 dBm
Sub-Harmonics			-60 dBc
Harmonic		-25 dBc	-20 dBc
Spurious		-75 dBc	-70 dBc
Phase Locked Indicator (Lock)		TLL "High"	
DC Voltage		+12 V _{DC}	+15 V _{DC}
DC Supply Current		400 mA	
Frequency Stability (Externally Referenced)*	Same as reference		
Specification Temperature		+25°C	
Operating Temperature	-40°C		+70°C

*For externally referenced phase locked oscillators, phase noise is reference source dependent, in General. Phase Noise = Reference Source + 20 Log (N) + 3 dB. The phase noise data shown here is tested with Wenzel model 501-27501-32

ECCN

EAR99

FEATURES

- High Output Power
- Low Phase Noise
- Low Harmonic Components

APPLICATIONS

- Radar Systems
- Communication Links
- Transmitters/Receivers

SUPPLEMENTAL DETAILS



Item	Specification
RF Output	SMA (F) Connector
REF Input	SMA (F) Connector
DC Bias Port (Vcc)	Feedthru Pin
Phase Lock Indicator Port (LT)	Feedthru Pin
Ground Terminal	Ground Lug
Case Material	Aluminum
Finish	Nickel Plated and Bare Aluminum
Package	Hermetically Sealed
Weight	4.0 Oz
Size	2.25" (L) x 2.25" (W) x 0.62" (H)
Outline	OP-EC-SM3

The drawing shows the mechanical specifications of the ERA-100000000X antenna. The top view (left) shows a rectangular board with dimensions 2.25 [57.2] x 2 x 2.07 [52.6]. It features a central label with the part number M/N: 1000000000X and S/N: 1000000000X. The board has four mounting holes (4 x Ø0.13 [3.2] THRU) and two coaxial connectors labeled REF IN and RF OUT. The side view (right) shows the antenna's profile with dimensions 2 x 0.50 [12.6] and 2 x 0.12 [3.1]. It also shows the mounting holes (2 x 0.41 [10.4]) and the antenna element (2 x 0.53 [13.6]).

Top View Dimensions:

- Overall Width: 2.25 [57.2]
- Overall Height: 2 x 2.07 [52.6]
- Mounting Hole Diameter: 4 x Ø0.13 [3.2] THRU
- Coaxial Connectors: REF IN, RF OUT

Side View Dimensions:

- Antenna Element Height: 2 x 0.53 [13.6]
- Mounting Hole Diameter: 2 x 0.41 [10.4]
- Antenna Element Width: 2 x 0.12 [3.1]
- Antenna Element Thickness: 2 x 0.50 [12.6]

NOTE:

- Eravant reserves the right to change the information presented without notice.
- Other mechanical configurations are available under different model numbers.

CAUTION:

- Exceeding absolute maximum ratings shown will damage the device.
- The device is static sensitive. Always follow ESD rules when working with the device.
- The case temperature of the device should never exceed **+70 °C**. Use proper heatsink or fan if necessary.
- Proper torque should be applied: 8.0 ± 0.15 inch-pounds (0.90 ± 0.02 Nm). Torque wrench model SCH-08008-S1 is highly recommended.

ERAVANT
MAKING MILLIMETERWAVE ACCESSIBLE

ERAVANT
MAKING MILLIMETERWAVE ACCESSIBLE