


STA-30-28-FS-40

Ka-Band Fixed Attenuator, 30 dB, 10 Watts

STA-30-28-FS-40 is a 10 watt fixed attenuator that is used in millimeterwave systems and operates from 26.5 to 40 GHz. The attenuator has a nominal fixed attenuation value of 30 dB across the entire Ka band. The attenuator is uniquely designed and fabricated for full waveguide band applications and displays an extremely flat frequency response across the full bandwidth. Other attenuation values are available under different model numbers as **STA-XX-28-FS-40**, where **XX** is the desired attenuation value.



Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency Range	26.5 GHz		40 GHz
Attenuation Range		30 dB	
Return Loss		20 dB	
Power Handling		10 W (CW)	12 W (CW)
Specification Temperature		+25°C	
Operating Temperature	-40°C		+85°C

Mechanical Specifications:

Item	Specification
Waveguide Ports	WR-28 Waveguide with UG-599/U Compatible Flange
Attenuation Setting	Fixed
Insertion Length	6.5"
Material	Aluminum
Finish	Gold Plated
Weight	9.5 Oz
Outline	TA-FA-40

ECCN

EAR99

FEATURES

- Full Band Coverage
- Low Cost

APPLICATIONS


- Test Lab
- Instrumentations
- System Integration

SUPPLEMENTAL DETAILS




STA-30-28-FS-40

Typical Performance vs. Frequency



Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTE:

- All data presented is collected from a sample lot. Actual data may vary unit to unit, slightly.
- All testing was performed under +25 °C case temperature.
- Eravant reserves the right to change the information presented without notice.

CAUTION:

- Exceeding absolute maximum ratings will damage the device.
- Any foreign objects in the waveguide will cause performance degradation and may damage the device.