

SWB-05045L-TB-1.0

WR-05 Waveguide Twist, 45° Left-Handed, 1.0” Long

SWB-05045L-TB-1.0 is a 45 degree, WR-05 left-handed waveguide twist with UG-387/U-M anti-cocking flanges. The length of the twist is 1”. The waveguide twist is manufactured through a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 140 to 220 GHz. Additional lengths may be available in stock, please contact us to inquire further.



Mechanical Specifications:

Item	Specification
Waveguide Size	WR-05 Waveguide with UG-387/U-M Anti-Cocking Flange
Twist Angle	45°
Twist Orientation	Left-Handed
Insertion Length	1.0”
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	0.6 Oz
Outline	WB-TG-5-A-L-2

ECCN

EAR99

FEATURES

- Frequency Range: 140 to 220 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

APPLICATIONS


- Test Instrumentations
- Sub-assemblies
- Lab Use

SUPPLEMENTAL DETAILS



SWB-05045L-TB-1.0

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTE:
LENGTH "L" IS CUSTOMIZABLE

NOTE:

- Eravant reserves the right to change the information presented without notice.

CAUTION:

- Any foreign objects in the waveguide will cause performance degradation and may damage or destroy the unit.