SWG-04012-FB-WP

WR-04 Straight Waveguide Section, 1.2”

SWG-04012-FB-WP is a 1.2” long, WR-04 straight waveguide section with UG-387/U-M anti-cocking flanges. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 170 to 260 GHz.



Mechanical Specifications:

Item	Specification
Waveguide Size	WR-04 Waveguide with UG-387/U-M Anti-Cocking Flange
Insertion Length	1.2”
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	0.6 Oz
Outline	WG-F04-A-L

ECCN

EAR99

FEATURES

- Frequency Range: 170 to 260 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

APPLICATIONS

- Test Instrumentation
- Sub-assemblies

SUPPLEMENTAL DETAILS

MAKING MILLIMETERWAVE ACCESSIBLE

Copyright © 2023 by Eravant

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTE:

- Eravant reserves the right to change the information presented without notice.

MAKING MILLIMETERWAVE ACCESSIBLE

Copyright © 2023 by Eravant