

# WR-05 Straight Waveguide Section, 1.5"

**SWG-05015-FB** is a 1.5" long, G-band straight waveguide section with a WR-05 waveguide and UG-387/U-M anti-cocking flanges. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 140 to 220 GHz.



**Mechanical Specifications:** 

Item	Specification
Waveguide Size	WR-05 Waveguide with UG-387/U-M Anti-Cocking Flange
Insertion Length	1.5"
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	0.7 Oz
Outline	WG-FG-A-L

#### **ECCN**

EAR99

## **FEATURES**

- Frequency Range: 140 to 220 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

### **APPLICATIONS**

- Test Instrumentation
- Sub-assemblies


SUPPLEMENTAL DETAILS

MAKING MILLIMETERWAV<mark>E ACCESSIBLI</mark>





Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTES:

LENGTH "L" IS CUSTOMIZABLE

<u>-Making millimeterwaye accessible</u>

#### NOTE:

Eravant reserves the right to change the information presented without notice.

# ERAFANT

MAKING MILLIMETERWAVE ACCESSIBLE