

WR-05 Straight Waveguide Section, 2.25"

SWG-05023-FB-2.25 is a 2.25" long, G-band straight waveguide section with a WR-05 waveguide and UG-387/U-M anti-cocking flanges. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 140 to 220 GHz.



Mechanical Specifications:

Item	Specification
Waveguide Size	WR-05 Waveguide with UG-387/U-M Anti-Cocking Flange
Insertion Length	2.25"
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	0.7 Oz
Outline	WG-FG-L

ECCN

EAR99

FEATURES

- Frequency Range: 140 to 220
 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

APPLICATIONS

- Test Instrumentation
- Sub-assemblies


SUPPLEMENTAL DETAILS

MAKING MILLIMETERWAV<mark>E ACCESSIBL</mark>





Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTE:

LENGTH "L" IS CUSTOMIZABLE

MAKING MILLIMETERWAVE ACCESSIBLE

NOTE:

Eravant reserves the right to change the information presented without notice.

ERAFANT

MAKING MILLIMETERWAVE ACCESSIBLE