

0.141" Diameter Circular Waveguide Section, 1"

SWG-141010-FB is a 1" long, V-band straight waveguide section with 0.141" diameter circular waveguide with UG385/U-M flange. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 58 to 68 GHz and extended frequency range of 50 to 75 GHz if the dominate TE₁₁ mode is maintained.



Mechanical Specifications:

Item	Specification
Waveguide Size	0.141" Diameter Circular Waveguide with UG-385/U-M Flange
Insertion Length	1.0"
Flange Material	Brass
Waveguide Material	Brass
Finish	Gold Plated
Weight	0.8 Oz
Outline	WG-FV-141-L

ECCN

EAR99

FEATURES

- Frequency Coverage: 58 to 68 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

APPLICATIONS

- Test Instrumentation
- · Sub-assemblies


SUPPLEMENTAL DETAILS

MAKING MILLIMETERWAV<mark>E ACCESSIBLE</mark>





Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



NOTES:

1. "L" IS A CUSTOMIZABLE LENGTH

NOTE:

- On condition that test data is provided it is collected from a sample lot. Actual data may vary slightly from unit to unit. All
 testing is performed under +25 °C room temperature.
- On condition that simulated test data is provided, actual measured data may slightly vary.
- Eravant reserves the right to change the information presented without notice.

CAUTION:

• If a waveguide is present, any foreign objects in the waveguide will cause performance degradation and may damage or destroy the unit.

ERAFANT

MAKING MILLIMETERWAVE ACCESSIBLE