SWG-28040-FB-WPC

WR-28 Straight Waveguide Section, 4”

SWG-28040-FB-WPC is a 4” long, WR-28 straight waveguide section with UG-599/U flanges. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 26.5 to 40 GHz.



Mechanical Specifications:

Item	Specification
Waveguide Size	WR-28 Waveguide with UG-599/U Flange
Insertion Length	4”
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	0.6 oz
Outline	WG-FA-L

ECCN

EAR99

FEATURES

- Frequency Range: 26.5 to 40 GHz
- Rugged Waveguide
- Low Insertion Loss

APPLICATIONS

- Test Instrumentation
- Sub-Assemblies

SUPPLEMENTAL DETAILS

Copyright © 2026 by Eravant

Mechanical Outline:

Unless otherwise specified, all dimensions are in inches [millimeters])



NOTES:

1. "L" IS A CUSTOMIZABLE LENGTH

NOTE:

- Eravant reserves the right to change the information presented without notice.

CAUTION:

- If a waveguide is present, any foreign objects in the waveguide will cause performance degradation and may damage or destroy the unit

NEXT GENERATION MILLIMETERWAVE COMPONENTS

Copyright © 2026 by Eravant