

## SWG-34013-FB-1.25

### WR-34 Straight Waveguide Section, 1.25"

**SWG-34013-FB-1.25** is a 1.25" long straight waveguide section with a WR-34 waveguide and UG-1530/U square flanges. The straight waveguide is manufactured with a precision machining process to ensure high quality and ruggedness. The waveguide is offered to cover the frequency range of 22 to 33 GHz.



#### Mechanical Specifications:

Item	Specification
Waveguide Size	WR-34 Waveguide with UG-1530/U Flange
Insertion Length	1.25"
Flange Material	Brass
Waveguide Material	Copper
Finish	Gold Plated
Weight	1.0 Oz
Outline	WG-F3-L

#### ECCN

EAR99

#### FEATURES

- Frequency Range: 22 to 33 GHz
- Rugged Waveguide Configuration
- Low Insertion Loss

#### APPLICATIONS


- Test Instrumentation
- Sub-assemblies

#### SUPPLEMENTAL DETAILS



## SWG-34013-FB-1.25

**Mechanical Outline:** (Unless otherwise specified, all dimensions are in inches [millimeters])



**NOTE:**  
LENGTH "L" CAN BE CUSTOMIZABLE.

**NOTE:**

- On condition that test data is provided it is collected from a sample lot. Actual data may vary slightly from unit to unit. All testing is performed under +25 °C room temperature.
- On condition that simulated test data is provided, actual measured data may slightly vary.
- Eravant reserves the right to change the information presented without notice.

**CAUTION:**

- If a waveguide is present, any foreign objects in the waveguide will cause performance degradation and may damage or destroy the unit.