

E-Band Waveguide Termination Load, 0.5 Watts

Description:

Model SWL-1227-S1 is a low power, E-Band termination load that covers the frequency range of 60 to 90 GHz. The termination load exhibits a typical VSWR of 1.05:1. It is designed and manufactured to offer a good match for system applications. Custom levels of power handling are available under different model numbers.



Features:

- Full Waveguide Band Coverage
- Low VSWR
- Instrumentation Grade

Applications:

- Test Lab
- Instrumentations
- Sub-assemblies

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	60 GHz		90 GHz
VSWR		1.05:1	
Power Handling		0.5 W (CW)	2 W (CW)
Specification Temperature		+25°C	
Operating Temperature	-40°C		+85°C

Mechanical Specifications:


Item	Specification
Waveguide	WR-12 Waveguide
Flange	UG-387/U Flange
Size	1.50" (L) x 0.75" (Ø)
Waveguide Material	Brass
Finish	Gold Plated
Weight	0.86 Oz
Outline	WL-EL






E-Band Waveguide Termination Load, 0.5 Watts

Typical Return Loss vs. Frequency



Mechanical Outline: (Unless otherwise specified, all dimensions are in inches)



Note:

- All data are presented using a limited sample lot. Actual data may vary unit to unit.
- All testing was performed under 25°C case temperature.
- Eravant reserves the right to change the information presented without notice.

Caution:

- Any foreign objects in the waveguide will degrade performance and/or damage the device.

