

WR-28 to Circular Waveguide Mode Transition, 0.328" Diameter

Description:

Model SWT-28328-SA-595 is a WR-28 to 0.328" diameter circular waveguide mode transition with UG-595/U flanges. The mode transition is manufactured by either EDM machining or electro-forming techniques to ensure high accuracy and a quality surface finish. The transition only induces a fraction of a dB insertion loss and offers a return loss of 32 dB or better. The nominal operating frequency is 24 to 33 GHz. The dominate mode frequency range can be extended to cover 24 to 42 GHz if the higher order waveguide mode is not excited.



Features:

- Rugged Waveguide Configuration
- Low Insertion Loss
- Instrumentation Grade
- Low Return Loss


Applications:

- Test Labs
- Test Instrumentation
- Sub-assemblies

Mechanical Specifications:

Item	Specification
Waveguide Size	WR-28 Waveguide with UG-595/U Flange
Waveguide Size	0.328" Diameter Circular Waveguide with UG-595/U Flange
Material	Aluminum
Finish	Gold Plated
Weight	0.85 Oz
Insertion Length	2.0"
Outline	WT-AC-328-595

Mechanical Outline: (Unless otherwise specified, all dimensions are in inches [millimeters])



Note:

- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.
- Other mechanical configurations are available under different model numbers.



www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com